



MB, ON, QC & Maritime Provinces: 800-299-9769  
 AB, SK, Northern Territories: 800-530-8640  
 British Columbia: 866-347-6911 | www.ltlutilitysupply.com

**OVERSTOCK CLEAROUT**  
 Call for Pricing | While Quantities Last!

PART #	DESCRIPTION	QTY
2059	1/0 35kV Insulated Jumper Cable Orange	339
2756	2/0 15 kV Insulated Jumper Cable Orange	468
2757	4/0-15K Insulated Jumper Cable Orange	142
3406	10" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-3/8" HUB FOR 3/4" & 1" RODS - 4000 FT. LB.	1019
03706	Pole Choker 1.90m 4 Pole Fall Arrest	1
6600	Generator Yamaha Model EF6600DE Part #YMS4AP1040LT. Each Generator comes w/ 10W40 1L bottle of engine oil	7
9898	1-1/4in Fiberglass Coupler. Salisbury	50
9998	Pole Mounted Contact Bar. No Connection. 40IN Chain w/ Adjustable Wheel Binder for Hanging Ground Sets	58
43177	Hydraulic Chainsaw. Long Reach 88IN	4
69437	Small Amp Gun Complete	4
69612	ASSY-POWER UNIT for Ampact Tool 69437 & 69611	10
04451W	LMG1000 Little Mule Wire Grip . 1000lbs capacity 18awg-1/0kcmil	18
1000IS	Generator Yamaha Model EF1000IS Part #YMS4AP1040LT Each Generator comes w/ 10W40 1L bottle of engine oil	4
2302B10009CA	Impact C.S.A. Gas meter Full Datalog w/ Pump	3
3512AB	10" SOCKET ANCHOR 10000 FT. LB. FOR 3/4" AND 1" RODS	284
7603CGA	Concentric Neutral Ground Clamp Salisbury	200
83280-U	Voltage Detector and Phasing Set (300V-35KV)	1
88G-D24-OH	Bashlin Lineman Body Belt (Hip Grip) Size 24	2
88G-D25-OH	Bashlin Lineman Body Belt (Hip Grip) Size 25	1
88G-D26-OH	Bashlin Lineman Body Belt (Hip Grip) Size 26	2
88G-D28-OH	Hip Grip Lineman Belt;CSA approved; Size28	1
C20009M-BR-D26	Buckingham Full Float Body Belt Brown Size D26 w/5 1/2IN foam cushioned pad reinforced w/rawhide lace. The floating dees provide 4IN lateral movement to reduce the wear on the pole strap	1
C2000M-BL-D23	Buckingham Full Float Body Belt Black Size D23 w/5 1/2IN foam cushioned pad reinforced w/rawhide lace. The floating dees provide 4IN lateral movement to reduce the wear on the pole strap	1
C2000M-BL-D25	Buckingham Full Float Body Belt Black Size D25 w/5 1/2IN foam cushioned pad reinforced w/rawhide lace. The floating dees provide 4IN lateral movement to reduce the wear on the pole strap	1
C2000M-BL-D26	Buckingham Full Float Body Belt Black Size D26 w/5 1/2IN foam cushioned pad reinforced w/rawhide lace. The floating dees provide 4IN lateral movement to reduce the wear on the pole strap	1
C2000M-BR-D24	Buckingham Full Float Body Belt Black Size D24 w/5 1/2IN foam cushioned pad reinforced w/rawhide lace. The floating dees provide 4IN lateral movement to reduce the wear on the pole strap	2
C4033220	Tel-O-Pole Grounds Tester includes: Self-contained carry case.Ball-stud terminals.Instruction manual.2 Troubleshooting probes.Self-test cable	2
C6002316	3 Way Ground Clamp Aluminum Drilled Terminal w/Eyescrew Handle for truck-grounding, industrial metalclad switchgear, substation buswork, overhead, underground and substation switches and three-phase ground sets	75
CRIMP12T-P	Battery POWERED CRIMPING TOOL 12 TON (tool only)	1
EF2800I	Generator Yamaha Model EF2800i Part #YMS4AP1040LT Each Generator comes w/ 10W40 1L of engine oil	14
GFR2L	Shovel; Roundpoint Blade; 48IN Ash Long Handle	165
H18762	Extention Resistors-1 Pair (48 or 80 kV)32in. For extending any CHANCE 16 kV Phasing Tester for 48 or 80 kV applications. Thread on	2
IFR5B-L+LAMP+HVS	Complete Suit Including Lamp and ventilation 3 .Inherently FR Arc Flash ORC5 (65+ cal) Tan. Set; Coat; Bib and Hood w/Cap; Large; w/Lamp; w/Air System	2
IFR5B-XL+HVS	ARC65 Bib/Coat Set w/air system Xlarge Tan Inherently FR ARC Series Arc Flash ORC5 (65+ cal)	1
JR150	CHAINSAW SHEATH Dielectric approved	13
LF46SE-UEN-P	Universal Insulator; 46KV Comes with Eyenut	266
LN15SE-U	15 kV Silicone Line Post Insulator Universal line post insulator	212
LN46SE-UEN-P	46kV Silicone Line Post Insulator Universal	226
LTL423B-S	Lineman 3IN Glove Winter Lined Black Size S. Kevlar stitched	257
LTL423IBFL-M	Lineman 3IN Glove Water Resistant Black Size M. Kevlar stitched	117
LTL423IBFL-S	Lineman 3IN Glove Water Resistant Black Size S 3IN Cuff Lineman Glove Inseam Fleece Lined. Kevlar stitched	173
LTL423IB-S	Lineman 3IN Glove Water Resistant Black Size S. Kevlar stitched	419
LTL426BFL-S	Lineman 6IN Glove Water Resistant Black Size S. Kevlar stitched	238
LTL426BFRL-M-1/2	Lineman 6IN FR Lined Winter Glove Black Size M. Kevlar stitched	193
LTL426B-S	Lineman 6IN Glove Water Resistant Black Size S. Kevlar stitched	238
LTL426B-XL	Lineman 6IN Glove Water Resistant Black Size XL. Kevlar stitched	181
LTL426IBFL-S	Lineman 6IN Glove Water Resistant Black Size S. Fleece Lined. Kevlar stitched	170
LTL426IBFRL-S-1/2	Lineman FR Lined Winter Glove 6in Cuff Black S. Kevlar stitched	194
LTLOUTRPAD	Outrigger pads. Composite material.	390
MS-391	20in Bar Chainsaw Stihl	6
PA-7181	S&C Cypoxy Insulator 13.8 kV (PA-7181)	252
PATMD68LICUTKIT1	Burndy PAT MD68 Inline Crimper with Cutter Jaw	5
RYA26UK	Burndy Underground URD Mole Terminal Kit KIT for 2/0 cable	12
SA-40726-1	S&C REPLACEMENT YELLOW ARC COMPRESSR AND CONTACT COVER	168
STCARRYCASE	Carry Case for MS-391 Chainsaw Orange	17
TCG6B-XL-HVS	Oberon 100 CAL Arc Flash Clothing Set ITH HVS AIR SYSTEM : Contains a TCG100 Hood with Hard Cap + TCG100 Bib-Overall + TCG100 Coat : Hi-Vis striping for added increased visibility AND True Color Grey Arc Flash Hood Window	1
UC2	Connector- SU system Line Hose For use on voltages through 34.5kV. Cass 4 Superior SAlCOR Type II elastomer; it is resistant to the effects of ozone and ultraviolet deterioration. It remains flexible even at sub-zero temperatures. (I.D 2IN x 10.5IN long x 7.75IN) Orange	28
WCY53	WEJTAP Aluminum Connector Installed With Yellow Booster 1/0 (6/1) AWG-266.8 (26/7) kcmil 4/0 AWG-450 kcmil, 4/0 (6/1) AWG- 397.5 (26/7) kcmil, 1/0 AWG- 300 kcmil	400
WCY61	WEJTAP Aluminum Connector Wejtap 0.94-0.68(Run) 0.94-0.68(Tap)	360
YGH29C26	Copper Compression C Connector, 3/0 AWG(Str) - 250 kcmil, 1/2" or 5/8" Rod (Run) & 6 AWG(Sol) - 2/0 AWG(Str) (Tap)	588
YJA2/02N	2/0 Two hole Nema Aluminum compression Terminal Lug	1000
YJA6CT12	#6 Single hole Aluminum compression Terminal 1/2IN stud	363